

## U.S. Architectural Products, Inc.

111 7 Douglas Avenue  
N. Providence, RI 02904  
(800) 243-6677  
Fax: (401) 725-8540

# PLYCEM<sup>®</sup> CEMDECK<sup>™</sup>

**Noncombustible, Structural, Fiber Reinforced Cement Board**

## **PACKAGING & WEIGHT SPECIFICATIONS**

ITEM	NOMINAL DIMENSION	PCS. / SQ.FT. PER CRATE 4' x 8'	Sq. ft. Per T/L 4' x 8'	PCS. / SQ.FT. PER CRATE 4' x 10'	Sq. ft. Per T/L 4' x 10'	WEIGHT PER SQ. FT.
17 mm	5/8"	26 / 832	9,984	21 / 840	10,080	4.25 lbs.
20 mm	3/4"	22 / 704	8,448	18 / 720	8,640	5.0 lbs.
22 mm	7/8"	20 / 640	7,680	16 / 640	7,680	5.5 lbs.
25 mm	1"	18 / 576	6,912	14 / 560	6,720	6.25 lbs.
30 mm	1 3/16"	15 / 480	5,760	12 / 480	5,760	7.5 lbs.

1. PLYCEM CEMDECK standard production is factory sealed with tongue and groove profile on the boards' long dimensions.
2. Standard sizes are 4' x 8' (stocked size) and 4' x 10' (special order). Maximum width is 4 ft. and maximum length is 10 ft.
3. 12 crates per truckload for 4' x 8' boards; 10 crates per truckload for 4' x 10' boards.
4. Sales of less than full crate quantities require a re-crating charge.
5. Lead time for any materials not in stock at our warehouses is 4-6 weeks.